

N13 – Sanitary Appliances and Fittings

Product Reference: Rearo Rapidfit HPL Vanity Unit

Manufacturer: Rearo Laminates
Address: 29 Loanbank Quadrant, Glasgow G51 3HZ
T: 0141 440 0800
E: commercial@rearo.co.uk
Web: www.rearocommercial.co.uk

Vanity Top:

- Height (overall): Standard 800mm FFL to the vanity bed.
- Floor Clearance: 100mm Shadow gap clearance.
- Depth: 600mm deep
- Core material: Moisture Resistant MDF with High pressure laminate (HPL) to the face.
- Thickness: 20mm.
- Colour: From the Rearo Rapidfit range.
- Edge treatment: Front edge postformed, to include 200mm single postformed downstand lipped with 2mm PVC edging. Including double postformed 100mm upstand to the rear.
- Wall Support: Softwood framing by others

Shadow Gap:

- Panel Height: approx. 650mm high, to suit the height of the vanity unit.
- Core material: Moisture Resistant MFC
- Thickness: 19mm.
- Colour: From the Rearo Rapidfit range.
- Edge treatment: All edges lipped with 2mm PVC edging

Access Panels:

- Panel Height: 450mm high,
- Core material: Moisture Resistant MFC
- Thickness: 19mm.
- Colour: From the Rearo Rapidfit range.
- Edge treatment: All edges lipped with 2mm PVC edging

Fittings:

- Clips: Lift on off ke-ku clips supplied as standard. Complete with fixings.
- Push on off clips are available upon request
- Décor ends to be fitted on site where vanity units are corner sited
- Shadow gap panel includes cut outs for access, number of cut outs to suit the number of sinks.

INSTALLATION

- *Programming: Do not install cubicles or duct/ wall panels before building is weathertight, wet trades have finished their work, wall and floor finishes are complete, and the building is well dried out.*
- *Accuracy: Set out to ensure frames and/ or panels and doors are plumb, level and accurately aligned.*
- *Modifications: Do not cut, plane or sand prefinished components except where shown on drawings.*
- *Fixing: Secure components using methods and fasteners recommended by the cubicle/ panel manufacturer. Prevent pulling away, bowing or other distortions to frames, panels and doors.*
- *Moisture and thermal movement: Make adequate allowance for future movement.*

N13 – Sanitary Appliances and Fittings

Product Reference: Rearo Rapidfit Compact Grade Vanity Unit

Manufacturer: Rearo Laminates
Address: 29 Loanbank Quadrant, Glasgow G51 3HZ
T: 0141 440 0800
E: commercial@rearo.co.uk
Web: www.rearocommercial.co.uk

Vanity Top:

- Height (overall): Standard 800mm FFL to the vanity bed.
- Floor Clearance: 100mm Shadow gap clearance.
- Depth: 600mm deep
- Core material: 12mm Compact Grade Laminate with High Pressure Laminate (HPL) to the face.
- Thickness: 13mm.
- Colour: From the Rearo Rapidfit range.
- Edge treatment: Front edge postformed, to include 200mm single postformed downstand lightly sanded.
- Includes loose 100mm upstand to the rear.
- Blocked ends are plant on compact grade panels fixed in place in production.
- Wall Support: Softwood framing by others

Shadow Gap:

- Panel Height: approx. 650mm high, to suit the height of the vanity unit.
- Core material: 12mm Compact Grade Laminate
- Thickness: 12mm.
- Colour: From the Rearo Rapidfit range.
- Edge treatment: All exposed edges to be bullnosed. Others lightly sanded

Access Panels:

- Panel Height: 450mm high,
- Core material: 12mm Compact Grade Laminate
- Thickness: 12mm.
- Colour: From the Rearo Rapidfit range.
- Edge treatment: All exposed edges to be bullnosed. Others lightly sanded

Fittings:

- Clips: Push on off ke-ku clips supplied as standard due to 12mm compact grade shadow gap. Complete with fixings.
- Lift on off clips are available upon request
- Décor ends to be fitted on site where vanity units are corner sited
- Shadow gap panel includes cut outs for access, number of cut outs to suit the number of sinks.

INSTALLATION

- *Programming: Do not install cubicles or duct/ wall panels before building is weathertight, wet trades have finished their work, wall and floor finishes are complete, and the building is well dried out.*
- *Accuracy: Set out to ensure frames and/ or panels and doors are plumb, level and accurately aligned.*
- *Modifications: Do not cut, plane or sand prefinished components except where shown on drawings.*
- *Fixing: Secure components using methods and fasteners recommended by the cubicle/ panel manufacturer. Prevent pulling away, bowing or other distortions to frames, panels and doors.*
- *Moisture and thermal movement: Make adequate allowance for future movement.*