

K32 – Panel Cubicles

Product Reference: Rearo Rapidfit MFC IPS Panels

Manufacturer: Rearo Laminates
Address: 29 Loanbank Quadrant, Glasgow G51 3HZ
T: 0141 440 0800
E: commercial@rearo.co.uk
Web: www.rearocommercial.co.uk

Panels:

- Height (overall): Standard up to 2900mm FFL
- Floor Clearance: 100mm
- Depth: Standard 250mm
- Core material: Moisture Resistant Melamine-Faced Chipboard (MR MFC)
- Thickness: 19mm
- Colour: From the Rearo Rapidfit colour chart
- Edge treatment: All edges lipped with 2mm PVC edging
- Wall Support: By others

Shadow Gap:

- Panel Height: 2800mm length.
- Core material: Moisture Resistant Melamine-Faced Chipboard (MR MFC).
- Thickness: 19mm.
- Colour: From the Rearo Rapidfit colour chart.
- Edge treatment: All edges lipped with 2mm PVC edging.

Fittings:

- Clips: Lift on off ke-ku clips supplied as standard. Complete with fixings.
- Push on off clips are available upon request

INSTALLATION

- *Programming: Do not install cubicles or duct/ wall panels before building is weathertight, wet trades have finished their work, wall and floor finishes are complete, and the building is well dried out.*
- *Accuracy: Set out to ensure frames and/ or panels and doors are plumb, level and accurately aligned.*
- *Modifications: Do not cut, plane or sand prefinished components except where shown on drawings.*
- *Fixing: Secure components using methods and fasteners recommended by the cubicle/ panel manufacturer. Prevent pulling away, bowing or other distortions to frames, panels and doors.*
- *Moisture and thermal movement: Make adequate allowance for future movement.*

K32 – Panel Cubicles

Product Reference: Rearo Rapidfit Impact IPS Panels

Manufacturer: Rearo Laminates
Address: 29 Loanbank Quadrant, Glasgow G51 3HZ
T: 0141 440 0800
E: commercial@rearo.co.uk
Web: www.rearocommercial.co.uk

Panels:

- Height (overall): Standard up to 2900mm FFL
- Floor Clearance: 100mm
- Depth: Standard 250mm
- Core material: Solid Grade Laminate (SGL) with Phenolic Core.
- Thickness: 12mm
- Colour: From the Rearo Rapidfit colour chart
- Edge treatment: All edges bullnosed / profiled as standard.
- Wall Support: By others

Shadow Gap:

- Panel Height: 2800mm length.
- Core material: Moisture Resistant Melamine-Faced Chipboard (MR MFC).
- Thickness: 19mm.
- Colour: From the Rearo Rapidfit colour chart.
- Edge treatment: All edges lipped with 2mm PVC edging.

Fittings:

- Clips: Lift on off ke-ku clips supplied as standard. Complete with fixings.
- Push on off clips are available upon request

INSTALLATION

- *Programming: Do not install cubicles or duct/ wall panels before building is weathertight, wet trades have finished their work, wall and floor finishes are complete, and the building is well dried out.*
- *Accuracy: Set out to ensure frames and/ or panels and doors are plumb, level and accurately aligned.*
- *Modifications: Do not cut, plane or sand prefinished components except where shown on drawings.*
- *Fixing: Secure components using methods and fasteners recommended by the cubicle/ panel manufacturer. Prevent pulling away, bowing or other distortions to frames, panels and doors.*
- *Moisture and thermal movement: Make adequate allowance for future movement.*

K32 – Panel Cubicles

Product Reference: Rearo Rapidfit Impact Shower IPS Panels

Manufacturer: Rearo Laminates
Address: 29 Loanbank Quadrant, Glasgow G51 3HZ
T: 0141 440 0800
E: commercial@rearo.co.uk
Web: www.rearocommercial.co.uk

Panels:

- Height (overall): Standard up to 2900mm FFL
- Floor Clearance: 100mm
- Depth: Standard 250mm
- Core material: Solid Grade Laminate (SGL) with Phenolic Core.
- Thickness: 12mm
- Colour: From the Rearo Rapidfit colour chart
- Edge treatment: All edges bullnosed / profiled as standard.
- Wall Support: By others

Shadow Gap:

- Panel Height: 2800mm length.
- Core material: Solid Grade Laminate (SGL) with Phenolic Core.
- Thickness: 12mm.
- Colour: From the Rearo Rapidfit colour chart.
- Edge treatment: Most edges left square and clean cut. Exposed edges are profiled

Fittings:

- Clips: Button type clips supplied for better fixing and maintenance.
- 4mm MDF ribs act as packer to allow Button type clips to sit flush with shadow gaps. Complete with fixings.
- Push on off clips and lift on / off are available upon request

INSTALLATION

- *Programming: Do not install cubicles or duct/ wall panels before building is weathertight, wet trades have finished their work, wall and floor finishes are complete, and the building is well dried out.*
- *Accuracy: Set out to ensure frames and/ or panels and doors are plumb, level and accurately aligned.*
- *Modifications: Do not cut, plane or sand prefinished components except where shown on drawings.*
- *Fixing: Secure components using methods and fasteners recommended by the cubicle/ panel manufacturer. Prevent pulling away, bowing or other distortions to frames, panels and doors.*
- *Moisture and thermal movement: Make adequate allowance for future movement.*