

K32 – Panel Cubicles

Product Reference: Rearo Lifeshield IPS

Manufacturer: Rearo Laminates
Address: 29 Loanbank Quadrant, Glasgow G51 3HZ
T: 0141 440 0800
E: commercial@rearo.co.uk
Web: www.rearocommercial.co.uk

Access Panels:

- Height (overall): Standard 2400 – 3000mm FFL
- Floor Clearance: 100mm / 150mm
- Depth: Standard 250mm
- Core material: 18mm MR MDF with compensator to reverse / 12mm SGL
- Thickness: 20mm / 12mm
- Colour: From the Rearo Rapidfit colour chart
- Edge treatment: All edges lipped with 2mm PVC edging / Profiled all around

Shadow Gap Box:

- Panel Height: 3000mm length.
- Core material: Moisture Resistant MDF with High pressure laminate (HPL) to the face.
- Thickness: 20mm.
- Colour: From the Rearo Rapidfit colour chart.
- Edge treatment: Vertical edges postformed, bottom edge lipped in laminate to assist against moisture ingress.
- Wall Support: By others
- Complete with cut outs for access
- Bare MR MDF skirting detail allows for vinyl flooring to be fixed to.

Fittings:

- Clips: Lift on off ke-ku clips supplied as standard. Complete with fixings.
- Push on off clips are not allowed within the healthcare industry

Accessories:

- Hinged access panels complete with budget locks are available. Contact the commercial department
- Push on off clips are available upon request

INSTALLATION

- *Programming: Do not install cubicles or duct/ wall panels before building is weathertight, wet trades have finished their work, wall and floor finishes are complete, and the building is well dried out.*
- *Accuracy: Set out to ensure frames and/ or panels and doors are plumb, level and accurately aligned.*
- *Modifications: Do not cut, plane or sand prefinished components except where shown on drawings.*
- *Fixing: Secure components using methods and fasteners recommended by the cubicle/ panel manufacturer. Prevent pulling away, bowing or other distortions to frames, panels and doors.*
- *Moisture and thermal movement: Make adequate allowance for future movement.*