

K32 – Panel Cubicles

Product Reference: Rearo Nursery Cubicles

Manufacturer: Rearo Laminates
Address: 29 Loanbank Quadrant, Glasgow, G51 3HZ
T: 0141 440 0800
E: commercial@rearo.co.uk
Web: www.rearocommercial.co.uk

Panels:

- Height (overall): Standard 1950mm FFL. Partitions 1000mm high – 1500mm high
- Floor Clearance: 150mm.
- Depth: Standard 1500mm
- Core material: Solid Grade Laminate (SGL) with Phenolic Core.
- Thickness: 12mm.
- Colour: From the Rearo Nursery & Rapidfit colour chart.
- Edge treatment: All edges bullnosed / profiled / shaped as standard.
- Wall Support: Nickel Powder Coated Aluminium U – Channel brackets with bolt through Fixings.

Pilasters:

- Panel Height: 1800mm
- Core material: Solid Grade Laminate (SGL) with Phenolic Core.
- Thickness: 12mm.
- Colour: From the Rearo Nursery & Rapidfit colour chart.
- Edge treatment: All edges bullnosed / profiled / shaped as standard.
- Ironmongery: Nickel Powder Coated Aluminium U – Channel brackets with bolt through Fixings.

Doors:

- Panel Height: 1000mm high – 1500mm high
- Core material: Solid Grade Laminate (SGL) with Phenolic Core. Pre-drilled to suit Hinge and Indicator bolt positions.
- Thickness: 12mm.
- Colour: From the Rearo Nursery & Rapidfit colour chart
- Edge treatment: All edges bullnosed / profiled as standard.
- Ironmongery: Indicator Bolt - Coin operated emergency release including keeper with concealed fixings.
Hinges - Nickel Powder Coated Aluminium bolt through hinges with nylon cams to set closed door position.
Anti finger trap for children. Coat Hook: Nickel Powder Coated Aluminium with buffer.

Fittings:

- Headrail: Nickel Powder Coated Aluminium 'U' section.
- Legs: Nickel Powder Coated Aluminium 150mm high adjustable legs.

Accessories:

- Outward Opening Keeper: Nickel Powder Coated Aluminium, to suit outward opening doors.

INSTALLATION

- *Programming: Do not install cubicles or duct/ wall panels before building is weathertight, wet trades have finished their work, wall and floor finishes are complete, and the building is well dried out.*
- *Accuracy: Set out to ensure frames and/ or panels and doors are plumb, level and accurately aligned.*
- *Modifications: Do not cut, plane or sand prefinished components except where shown on drawings.*
- *Fixing: Secure components using methods and fasteners recommended by the cubicle/ panel manufacturer. Prevent pulling away, bowing or other distortions to frames, panels and doors.*
- *Moisture and thermal movement: Make adequate allowance for future movement.*