

Rigid Sheet Fine Linings and Panelling – K13

Product Reference: Selkie MDF / Plywood Wall Panels

Manufacturer: Rearo Laminates
Address: 29 Loanbank Quadrant, Glasgow G51 3HZ
T: 0141 440 0800
E: commercial@rearo.co.uk
Web: www.rearocommercial.co.uk

Panels:

- Height: 2420mm.
- Width: 1200mm.
- Core material: 9mm BB/WG Birch Plywood / MR MDF
- Face: Rearo High Pressure Magnetic Laminate
- Compensator: Rearo Balancer High Pressure Laminate
- Thickness: 11mm
- Fire Rating: Class 2
- Colour: From Selkie Brochure (30 choices)
- Edge treatment: All edges square and clean cut / Long edges tongue and grooved
- Wall Support: Panel adhesive and mechanical fixings. All as per the manufacturers standard fitting instructions.

Accessories:

- Extrusions: 2450mm Long. SAA (Satin Anodised Aluminium), Black, White and Polished Chrome

INSTALLATION

- *Programming: Do not install wall panels before building is weathertight, wet trades have finished their work, wall and floor finishes are complete, and the building is well dried out.*
- *Accuracy: Set out to ensure frames and/ or panels and doors are plumb, level and accurately aligned.*
- *Modifications: Do not cut, plane or sand prefinished components except where shown on drawings.*
- *Fixing: Secure components using methods and fasteners recommended by the manufacturer. Prevent pulling away, bowing or other distortions to frames, panels and doors.*
- *Moisture and thermal movement: Make adequate allowance for future movement.*